


# Propafilm™ RBC



## Technical Data Sheet

### RBC - Acrylic Coated Film

- Biaxially oriented polypropylene (BOPP) film coated on both sides with an aqueous acrylic (chlorine free) dispersion.



- Acrylic Coating
- White Pigmented Oriented Polypropylene
- Acrylic Coating

### Features

- Low UV/visible light transmission giving improved protection against rancidity
- Enhanced print definition compared to transparent film
- Heat-sealable on both sides, with excellent hot tack aromas
- Excellent barrier to water vapour, gases and aromas
- Low sealing threshold and broad sealing range
- Both sides of the film are receptive to inks, adhesives and tear-tapes
- High gloss surface on both sides
- Special care should be taken when printing fine tone colours directly on to the film surface
- Exceptional puncture and impact-resistance properties are maintained even at low temperatures

### Applications

**RBC30(120)** is suitable for use in both plain and printed forms on high-speed overwrapping and form-fill-seal machinery. Particularly suited for use as a direct product overwrap or carton overwrap in the biscuit, bakery and confectionery industries.

### Technical Properties (Typical Values)

Property	Test Method	Test Conditions	Units	RBC	
Thickness	Innovia Films test		micron	30	
			gauge	120	
Yield	Innovia Films test		m <sup>2</sup> /kg	33.9	
			in <sup>2</sup> /lb	23850	
			g/m <sup>2</sup>	29.5	
Permeability to: Water vapour	ASTM F 1249	38°C 90% RH 100°F 90% RH	g/m <sup>2</sup> .24 hrs	5.0	
			g/100in <sup>2</sup> . 24 hrs	0.32	
Oxygen	ASTM F 1927	23°C 0% RH 73°F 0% RH	cc/m <sup>2</sup> .24 hrs	850	
			cc/100in <sup>2</sup> . 24 hrs	54.84	
Optical: Opacity	Innovia Films test		%	62	
Coefficient of friction (film to film)	ASTM D 1894	Static/ Dynamic		0.20-0.30	
				0.20-0.30	
Sealing range	Innovia Films test	2 secs; 0.10MN/m <sup>2</sup> 2 secs; 15 psi	°C	85-145	
			°F	185-295	
Seal strength	Innovia Films test	130°C; 2 secs; 0.10MN/m <sup>2</sup> 265°F; 2 secs; 15 psi	g(f)/25mm/ in	>400	
Shrinkage	Innovia Films test	60 secs at 120°C (250°F) 60 secs at 130°C (265°F)	%	MD	4.0
				TD	Nil
				MD	7.0
				TD	1.0

MD Machine Direction    TD Transverse Direction

All properties are tested under standard laboratory conditions: 23 ± 2°C, 50 ± 5% RH,(73 ± 4F, 50 ± 5% RH), unless otherwise stated. Where relevant, tests are based on international testing standards.

Ref B410 - 1 of 2 - 0222

# Propafilm™ RBC

## Technical Data Sheet

### Reel Specifications

#### Nominal Reel Diameters

Film	Single Length (metres)	12x Length (metres)
RBC30	1250	15000

Film	Single Length (feet)	12x Length (feet)
RBC120	4100	49200

Other reel lengths are available in multiples of the single length as per the core diameter listed below.

Outside Diameter	1x	2x	4x	6x	8x	12x
For 77mm / 3in core	240mm 9½in	330mm 13in	450mm 18in	-	-	-
For 153mm / 6in core	-	-	475mm 18¾in	570mm 22½in	650mm 25½in	785mm 31in

### Film Storage and Handling

The low heat-seal threshold and wide seal range of Propafilm™ RBC film allows its use in particularly demanding packaging machine applications. Care should therefore be taken to protect reels of film from storage temperatures above 30°C (85°F) and localised sources of heat above 45°C (115°F). Reels of Propafilm™ RBC should be protected from high levels of moisture and accidental water splashes at all times. The reels should remain in the protective coverings supplied until ready for use on converting or packaging machinery. Converted reels, in both master and slit reel form should be similarly protected at all times. Propafilm™ RBC is suitable for use for 6 months from the date of delivery and stocks should be used in rotation. Films should be allowed to reach operating room temperatures for 24 hours before use.

### Food Contact

Propafilm™ RBC complies with the applicable EU and US legislation for most applications involving direct contact with foods. Full details are given on the Declaration of Compliance. Customers intending to use Propafilm™ RBC in a food contact application should request a copy of this document from Innovia Films. Details of compliance with food contact legislation in non-EU countries are also available upon request.

### Health & Safety Guidelines

For Health & Safety information, please refer to literature reference B190.

**Disclaimer:** Innovia Films or any of its affiliated companies (hereinafter 'Innovia Films') declines any liability with respect to the use made by any third party of the information contained herein. The information contained herein represents Innovia Films' best knowledge thereon without constituting any express or implied guarantee or warranty of any kind (including, but not limited to, the accuracy, the completeness or relevance of the data set out herein). Innovia Films is the sole owner or authorised user of the intellectual property rights relating to the information communicated. The information relating to the use of the products is given for information purposes only. No guarantee or warranty is provided that the product is adapted to the client's specific use. The client should perform his own tests to determine the suitability for a particular purpose. The final choice of use of a product remains the sole responsibility of the client.

Ref B410 - 2 of 2 - 0222

#### Regional Offices:

Europe (UK) Tel +44 16973 42281  
Americas (USA) Tel +1 800 424 6273  
Asia-Pacific (Aus) Tel +61 3 9303 0600

[www.innoviafilms.com](http://www.innoviafilms.com)  
email: [packaging@innoviafilms.com](mailto:packaging@innoviafilms.com)  
™ Trademark of Innovia Films

